




WERNER FISCHER AG
STAHLROHRE

Rundrohre


diverse Legierungen nach EN AW



nach EN 573-3 / 754-2/-7/-8 / 755-1/-2/-7/-8/-9, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
6.0	1.00	0.04
7.0	1.50	0.07
8.0	1.00	0.06
8.0	1.50	0.08
10.0	1.00	0.08
10.0	1.50	0.11
10.0	2.00	0.14
10.0	3.00	0.18
12.0	1.00	0.09
12.0	1.50	0.13
12.0	2.00	0.17
12.0	3.00	0.23
13.0	1.50	0.15
13.0	3.00	0.25
14.0	1.00	0.11
14.0	2.00	0.21
14.0	2.50	0.24
15.0	1.00	0.12
15.0	1.50	0.17
15.0	2.00	0.23
16.0	1.00	0.13
16.0	1.50	0.19
16.0	2.00	0.24
16.0	2.50	0.28
16.0	3.00	0.33
18.0	1.00	0.15
18.0	1.50	0.21
18.0	2.00	0.28
18.0	2.50	0.33
18.0	3.00	0.38
18.0	4.00	0.48
19.0	1.00	0.15
20.0	1.00	0.16
20.0	1.50	0.24
20.0	2.00	0.31
20.0	2.50	0.37

Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
20.0	3.00	0.44
20.0	3.50	0.49
20.0	4.00	0.54
20.0	5.00	0.64
22.0	1.00	0.18
22.0	1.50	0.26
22.0	2.00	0.34
22.0	3.00	0.49
24.0	1.50	0.29
24.0	2.00	0.38
25.0	1.00	0.20
25.0	1.50	0.30
25.0	2.00	0.39
25.0	2.50	0.48
25.0	3.00	0.56
25.0	5.00	0.85
28.0	1.00	0.23
28.0	1.50	0.34
28.0	2.00	0.44
28.0	3.00	0.55
28.0	4.00	0.82
30.0	1.50	0.37
30.0	2.00	0.48
30.0	2.50	0.59
30.0	3.00	0.69
30.0	4.00	0.90
30.0	5.00	1.07
30.0	7.50	1.44
30.0	10.00	1.70
32.0	1.00	0.26
32.0	1.50	0.40
32.0	2.00	0.51
32.0	3.00	0.75
33.0	2.00	0.53
33.5	3.25	0.84
35.0	1.50	0.43



WERNER FISCHER AG
STAHLROHRE

Rundrohre




diverse Legierungen nach EN AW

nach EN 573-3 / 754-2/-7/-8 / 755-1/-2/-7/-8/-9, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
35.0	2.00	0.56
35.0	2.50	0.69
35.0	3.00	0.82
35.0	4.00	1.07
35.0	5.00	1.30
36.0	4.00	1.09
38.0	1.50	0.44
38.0	3.00	0.91
39.0	2.00	0.63
40.0	1.50	0.50
40.0	2.00	0.65
40.0	2.50	0.80
40.0	3.00	0.95
40.0	4.00	1.24
40.0	5.00	1.49
40.0	7.50	2.08
40.0	10.00	2.56
42.0	1.50	0.52
42.0	2.00	0.68
42.0	2.50	0.84
42.0	3.50	1.14
42.0	4.00	1.29
45.0	1.50	0.56
45.0	2.00	0.73
45.0	2.50	0.91
45.0	3.00	1.08
45.0	5.00	1.73
45.0	6.00	2.00
46.0	3.00	1.02
48.0	2.00	0.79
48.0	2.50	0.98
48.0	3.00	1.15
48.0	4.00	1.52
50.0	1.50	0.63

Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
50.0	2.00	0.82
50.0	2.50	1.02
50.0	3.00	1.21
50.0	4.00	1.56
50.0	5.00	1.91
50.0	8.00	2.85
50.0	10.00	3.42
50.0	12.50	4.00
50.0	15.00	4.48
54.0	2.00	0.90
55.0	2.00	0.90
55.0	2.50	1.11
55.0	5.00	2.16
56.0	3.00	1.35
58.0	3.00	1.40
58.0	4.00	1.85
60.0	1.50	0.75
60.0	2.00	0.98
60.0	2.50	1.22
60.0	3.00	1.46
60.0	4.00	1.93
60.0	5.00	2.33
60.0	6.00	2.80
60.0	10.0	4.27
60.0	15.00	5.76
65.0	2.00	1.09
65.0	2.50	1.35
65.0	5.00	2.59
65.0	10.00	4.66
66.0	3.00	1.60
70.0	2.00	1.17
70.0	2.50	1.44



WERNER FISCHER AG
STAHLROHRE

Rundrohre



Diverse Legierungen nach EN AW

Nach EN 573-3 / 754-2/-7/-8 / 755-1/-2/-7/-8/-9, Stangenlänge ca. 6 m


Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
70.0	3.00	1.70
70.0	4.00	2.28
70.0	5.00	2.76
70.0	10.00	5.13
70.0	15.00	7.05
70.0	20.00	8.54
75.0	2.50	1.57
75.0	5.00	3.02
76.0	2.50	1.59
76.0	3.00	1.84
80.0	2.00	1.35
80.0	2.50	1.67
80.0	3.00	2.00
80.0	4.00	2.63
80.0	5.00	3.20
80.0	10.00	5.98
80.0	15.00	8.33
80.0	20.00	10.25
83.0	5.00	3.33
84.0	2.00	1.42
85.0	5.00	3.39
86.0	3.00	2.15
90.0	2.00	1.52
90.0	3.00	2.25
90.0	4.00	2.92
90.0	5.00	3.63
90.0	10.00	6.78
90.0	15.00	9.67
90.0	20.00	11.96
100.0	2.00	1.69
100.0	2.50	2.11
100.0	3.00	2.49
100.0	4.00	3.32
100.0	5.00	4.06
100.0	6.00	4.78

Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
100.0	10.00	7.69
100.0	20.00	13.56
105.0	2.500	2.17
106.0	3.00	2.67
108.0	3.00	2.72
108.0	4.00	3.59
110.0	3.00	2.77
110.0	5.00	4.53
110.0	10.00	8.48
114.0	3.00	2.83
115.0	5.00	4.75
120.0	3.00	3.03
120.0	4.00	3.93
120.0	5.00	4.97
120.0	8.00	7.60
120.0	10.00	9.39
120.0	20.00	17.12
124.0	2.00	2.15
125.0	4.00	4.11
125.0	5.00	5.18
125.0	10.00	9.75
125.0	22.50	19.71
130.0	3.00	3.29
130.0	5.00	5.40
130.0	10.00	10.26
130.0	15.00	14.63
133.0	3.00	3.31
133.0	4.00	4.38
140.0	4.00	4.61
140.0	5.00	5.73
150.0	3.00	3.81
150.0	5.00	6.26
150.0	10.00	12.09
150.0	15.00	17.29



WERNER FISCHER AG
STAHLROHRE

Rundrohre



Diverse Legierungen nach EN AW

Nach EN 573-3 / 754-2/-7/-8 / 755-1/-2/-7/-8/-9, Stangenlänge ca. 6 m

Aussendurchmesser	Wandstärke	Gewicht
mm	mm	kg/m
150.0	25.00	26.49
150.0	40.00	37.30
156.0	3.00	3.98
159.0	4.00	5.26
160.0	4.00	5.29
160.0	5.00	6.69
160.0	10.00	12.72
160.0	15.00	18.44
168.0	3.50	4.88
170.0	5.00	6.99
180.0	5.00	7.56
180.0	15.00	20.98
180.0	25.00	32.85
180.0	55.00	58.29
180.0	70.00	65.28
200.0	5.00	8.42
200.0	20.00	30.52
200.0	50.00	63.59
208.0	4.00	6.92
210.0	5.00	8.68
219.0	4.00	7.30
240.0	30.00	53.84
250.0	5.00	10.58
250.0	50.00	84.78
258.0	4.00	8.61
273.0	4.50	10.24
300.0	4.00	10.04
300.0	60.00	122.00
323.9	5.50	14.85



WERNER FISCHER AG
STAHLROHRE

Vierkantrohre



EN AW-6060 T66 / AlMgSi0.5 F22, gepresst, nach EN 573-3 / 755-1/-2/-9, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
10 x 10	1.0	0.10
12 x 12	1.0	0.12
15 x 15	1.0	0.15
15 x 15	1.5	0.22
15 x 15	2.0	0.28
20 x 20	1.5	0.30
20 x 20	2.0	0.39
20 x 20	3.0	0.56
25 x 25	1.5	0.38
25 x 25	2.0	0.49
25 x 25	3.0	0.73
30 x 30	1.5	0.47
30 x 30	2.0	0.61
30 x 30	2.5	0.74
30 x 30	3.0	0.88
34 x 34	2.0	0.70
34 x 34	3.0	1.02
35 x 35	2.0	0.72
35 x 35	2.5	0.87
35 x 35	3.0	1.06
40 x 40	1.5	0.62
40 x 40	2.0	0.82
40 x 40	2.5	1.01
40 x 40	3.0	1.19
40 x 40	4.0	1.57
40 x 40	5.0	1.89
42 x 42	3.0	1.26
45 x 45	2.0	0.93
50 x 50	2.0	1.04
50 x 50	2.5	1.31
50 x 50	3.0	1.52
50 x 50	4.0	1.98
50 x 50	5.0	2.48

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
55 x 55	2.0	1.15
55 x 55	5.0	2.70
56 x 56	2.5	1.44
60 x 60	2.0	1.25
60 x 60	3.0	1.85
60 x 60	4.0	2.44
60 x 60	5.0	2.97
65 x 65	2.5	1.69
70 x 70	2.0	1.50
70 x 70	4.0	2.87
77 x 77	2.5	2.00
80 x 80	2.0	1.72
80 x 80	3.0	2.46
80 x 80	4.0	3.28
80 x 80	5.0	4.05
80 x 80	6.0	4.80
90 x 90	3.0	2.83
90 x 90	4.0	3.78
100 x 100	2.0	2.16
100 x 100	3.0	3.20
100 x 100	4.0	4.18
100 x 100	5.0	5.23
120 x 120	2.5	3.17
120 x 120	4.0	5.05
120 x 120	5.0	6.33
145 x 145	3.0	4.60
150 x 150	2.5	3.98
150 x 150	5.0	7.83



WERNER FISCHER AG
STAHLROHRE

Rechteckrohre



EN AW-6060 T66 / AlMgSi0.5 F22, gepresst, nach EN 573-3 / 455-2/-2/-9, Stangenlänge ca. 6m

Abmessung mm	Wandstärke mm	Gewicht kg/m
20 x 10	1.5	0.22
20 x 10	2.0	0.28
20 x 12	2.0	0.31
20 x 15	1.5	0.26
20 x 15	2.0	0.33
25 x 10	2.0	0.34
25 x 15	1.5	0.31
25 x 15	2.0	0.38
25 x 20	2.0	0.44
30 x 10	1.5	0.31
30 x 10	2.0	0.39
30 x 15	1.5	0.35
30 x 15	2.0	0.45
30 x 20	1.5	0.39
30 x 20	2.0	0.50
30 x 20	3.0	0.66
30 x 25	2.0	0.56
34 x 20	2.0	0.55
34 x 20	3.0	0.78
35 x 15	2.0	0.51
35 x 20	2.0	0.58
35 x 25	2.0	0.61
40 x 10	2.0	0.50
40 x 15	1.5	0.42
40 x 15	2.0	0.56
40 x 15	2.2	0.61
40 x 20	1.5	0.47
40 x 20	2.0	0.61
40 x 20	2.5	0.76
40 x 20	3.0	0.87
40 x 20	4.0	1.14
40 x 25	2.0	0.66
40 x 25	3.0	0.95

Abmessung mm	Wandstärke mm	Gewicht kg/m
40 x 30	2.0	0.71
40 x 30	2.5	0.89
40 x 30	3.0	1.04
40 x 30	4.0	1.34
45 x 20	2.0	0.67
45 x 25	2.0	0.71
45 x 34	3.0	1.18
50 x 15	2.0	0.67
50 x 20	2.0	0.72
50 x 20	3.0	0.92
50 x 20	4.0	1.36
50 x 25	2.0	0.72
50 x 25	2.5	0.95
50 x 25	3.0	1.13
50 x 30	2.0	0.82
50 x 30	2.5	1.03
50 x 30	3.0	1.21
50 x 34	3.0	1.29
50 x 40	2.0	0.93
50 x 40	2.5	1.17
50 x 40	3.0	1.37
50 x 40	4.0	1.77
50 x 45	2.0	0.98
55 x 35	3.0	1.37
55 x 45	2.0	1.02
56 x 31	2.5	1.11
60 x 20	2.0	0.82
60 x 20	3.0	1.22
60 x 20	4.0	1.56
60 x 25	2.0	0.89
60 x 25	3.0	1.25
60 x 30	2.0	0.96
60 x 30	3.0	1.37



WERNER FISCHER AG
STAHLROHRE

Rechteckrohre



EN AW-6060 T66 / AlMgSi0.5 F22, gepresst, nach EN 573-3 / 755-1/-2/-9, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
60 x 34	3.0	1.45
60 x 40	2.0	1.04
60 x 40	2.5	1.26
60 x 40	3.0	1.60
60 x 40	4.0	1.99
60 x 50	3.0	1.69
60 x 50	4.0	2.20
65 x 20	2.0	0.87
70 x 20	2.0	0.93
70 x 25	2.5	1.22
70 x 30	2.0	1.04
70 x 30	3.0	1.55
70 x 40	3.0	1.69
70 x 50	4.0	2.42
75 x 50	3.0	1.96
80 x 18	2.0	1.03
80 x 20	2.0	1.04
80 x 20	2.5	1.28
80 x 25	2.0	1.11
80 x 30	2.0	1.17
80 x 30	3.0	1.69
80 x 30	4.0	2.20
80 x 40	2.0	1.28
80 x 40	2.5	1.58
80 x 40	3.0	1.85
80 x 40	4.0	2.44
80 x 50	2.0	1.39
80 x 50	3.0	2.05
80 x 50	4.0	2.64
80 x 50	5.0	3.24
80 x 60	2.5	1.82
80 x 60	3.0	2.18
80 x 60	4.0	2.85
90 x 40	3.0	2.01

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
100 x 18	2.0	1.23
100 x 20	2.0	1.25
100 x 25	2.0	1.33
100 x 30	2.0	1.39
100 x 30	3.0	2.05
100 x 40	2.0	1.46
100 x 40	2.5	1.82
100 x 40	3.0	2.21
100 x 40	4.0	2.94
100 x 50	2.0	1.61
100 x 50	3.0	2.38
100 x 50	4.0	3.09
100 x 50	5.0	3.78
100 x 60	2.0	1.72
100 x 60	3.0	2.54
100 x 60	4.0	3.29
100 x 60	5.0	4.05
100 x 80	2.5	2.36
100 x 80	3.0	4.66
110 x 50	2.5	2.09
110 x 60	4.0	3.50
120 x 20	2.0	1.24
120 x 30	2.0	1.61
120 x 30	3.0	2.40
120 x 40	2.0	1.69
120 x 40	2.5	2.09
120 x 40	3.0	2.50
120 x 40	4.0	3.28
120 x 50	3.0	2.71
120 x 50	4.0	3.50
120 x 60	3.0	2.87
120 x 60	4.0	3.80
120 x 60	5.0	4.59
120 x 80	3.0	3.14



WERNER FISCHER AG
STAHLROHRE



Rechteckrohre

EN AW-6060 T66 / AlMgSi0.5 F22, gepresst, nach EN 573-3 / 755-1/-2/-9, Stangenlänge ca. 6m


Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
130 x 30	3.0	2.50
130 x 50	4.0	3.72
140 x 20	3.0	2.50
140 x 40	4.0	3.72
140 x 60	2.5	2.63
140 x 60	4.0	4.15
140 x 80	4.0	4.66
140 x 80	6.0	6.74
150 x 25	2.5	2.36
150 x 30	2.8	2.64
150 x 35	2.5	2.41
150 x 40	4.0	4.00
150 x 50	2.0	2.12
150 x 50	4.0	4.15
150 x 60	4.0	4.36
150 x 60	5.0	5.40
150 x 100	3.0	3.95
160 x 40	4.0	4.15
160 x 60	4.0	4.58
160 x 80	4.0	5.01
170 x 25	1.8	1.83
170 x 25	2.0	2.03
170 x 40	4.0	4.36
180 x 40	4.0	4.58
180 x 50	4.0	4.88
180 x 60	3.0	3.72
180 x 80	4.0	5.45
200 x 18	2.0	2.35
200 x 30	2.8	3.39
200 x 40	2.5	3.19
200 x 50	2.5	3.31
200 x 50	4.0	5.23
200 x 60	4.0	5.44

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
200 x 80	4.0	5.88
200 x 100	4.0	6.39
200 x 100	5.0	7.83
240 x 100	5.0	8.91
300 x 120	4.5	9.99



WERNER FISCHER AG
STAHLROHRE

Flach-Ovalrohre



EN AW-6060 T66 / AlMgSi0.5 F22, gepresst, nach EN 573-3 / 755-2/-8, Stangenlänge ca. 6m

Abmessung	Wandstärke	Gewicht
mm	mm	kg/m
22 x 12	2.0	0.28
30 x 15	2.0	0.38
36 x 16	2.0	0.45
44 x 17	2.0	0.55
50 x 20	3.0	0.95
60 x 25	2.5	0.97